48VDC surface /

suspended square track

1mt

Design: Ivela Design Team



27

3 23

J'MAR

CE +1850°

IP 20

Product Code	Color
6445-10-16	Black
General specifications	
Product type	Tracks
Mounting type	Wall / ceiling - surface
Indoor/Outdoor light	Indoor
Description	48V low voltage track for ceiling, wall or suspension applications, compatible with spotlights equipped with the specific 48V adapter. The two conductors can transmi also the DALI signal, allowing for the dynamic control of the single light sources. The continuity of the positive line between each element is important for a correc installation of all the accessories. Maximum load: 720W
Physical specifications	
Finishing	Extruded aluminium alloy, polyester painted.
Load capacity description	The track has a load capacity of 4 Kg every 1000 mm. For a 4 Kg load every 200 mm, a maximum fixing distance of 500 mm is recommended.
Electrical specifications	
Voltage (V)	48
Current (A)	15
Weight and dimension	
Length (mm)	1000
Height (mm)	21
Width (mm)	27
Accessories	
Product Code	6451-10-30
Name	Right live-end
Packaging quantity	10
Finishing	Black
Product Code	6451-11-30
Name	Left live-end
Packaging quantity	10
Finishing	Black
Product Code	6452-00-30
Name	Central connector
Packaging quantity	5
Finishing	Black
Product Code	6453-00-30
Name	Straight connector
Packaging quantity	25

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

50



Datasheet

50

59

















E-

Product Code 6454-10-30 Mechanical joint without electrical contacts Name Packaging quantity 25 Black Finishing 6455-10-30 Product Code Name Inside L joint Packaging quantity 5 Finishing Black Product Code 6455-11-30 Name Outside L joint 5 Packaging quantity Black Finishing Product Code 6464-10-30 Name Right T joint 90 Length (mm) Product Code 6464-11-30 Name Left T joint Length (mm) 90 6456-00-30 Product Code Flexible joint Name Packaging quantity 2 Black Finishing Product Code 6458-06-30 Name Suspension kit with steel wire 2000mm, plate 40mm Packaging quantity 10 Finishing Black 6458-00-30 Product Code Suspension kit with steel wire 2000mm, plate 40mm. Name Packaging quantity 10 Finishing Black 6459-20-30 Product Code Wall/ceiling pair Name 10 Packaging quantity Finishing Black Product Code 6463-00-00 Ceiling kit Name Product Code 6465-03-31 150W 220-240V/48VDC DALI electronic transformer, for remote use Name Finishing White Product Code 81-09000 100W 230V/48V PWM transformer for remote use Name

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY elcom

Datasheet

Product Code 81-09001 200W 230V/48V PWM transformer for remote use Name ti i Product Code 81-90122 300W 230V/48V PWM transformer for remote use Name Ď Product Code 81-90089 Name Bluetooth Casambi dimmer 48V 4 channels Product Code 81-90123 Name PWM dimmer Product Code 81-90124 Name DALI dimmer 81-90128 Product Code Name Bluetooth DALI Controller Product Code 6461-00-30 Name Track cover 1000mm Packaging quantity 10 Finishing Black 6460-00-30 Product Code Dead end Name Packaging quantity 10 Finishing Black 6503-10-30 Product Code Right live-end with integrated transformer (150W) Name 510 Black Finishing 32 Product Code 6503-11-30 47 Left live-end with integrated transformer (150W) Name 510 Finishing Black 32 Product Code 6504-10-30 Name Right live-end with integrated transformer (150W) DALI 510 Finishing Black 32 Product Code 6504-11-30 47 Left live-end with integrated transformer (150W) DALI Name 510 Finishing Black 32 Product Code 6505-10-30 30 Name Right live-end with integrated transformer (100W) 367 R Finishing Black 30


Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

ELCOM Srl MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY

47

47

elcom



Product Code Name

Finishing

Product Code

Name Finishing

Product Code

Name Finishing 6505-11-30 Left live-end with integrated transformer (100W) Black 6506-00-30 Live-end with integrated transformer for suspended track (150W) Black 6507-00-30 Live-end with integrated transformer for suspended track (150W) DALI Black

Power tolerance $\pm~5\%$ - Luminous flux tolerance $\pm~5\%$ - Measurement uncertainty $\pm~10\%$ - Ta: 25°C

