#### 48VDC TL Recessed track

#### 3mt

Design: Ivela Design Team



| <br>6 | 7 |   |    |
|-------|---|---|----|
| 2     | 7 | , |    |
|       |   |   | 23 |









| IP 20 | ) |
|-------|---|
|-------|---|



6446-30-30

Color Black

#### **General specifications**

Product type Tracks Ceiling - recessed Mounting type

Indoor/Outdoor light Indoor Description

48V low voltage electrified track for trimless recessed installation in false ceilings., compatible with spotlights equipped with the specific 48V adapter. The two conductors can transmit also the DALI signal, allowing for the dynamic control of the single light sources. The continuity of the positive line between each element is important for a correct installation of all the accessories.

Maximum load: 720W

#### **Physical specifications**

Finishing Extruded aluminium alloy, polyester painted. Load capacity description The track has a load capacity of 4 Kg every 1000 mm. For a 4 Kg load every 200 mm, a maximum fixing distance of 500 mm is recommended.

#### **Electrical specifications**

48 Voltage (V) 15 Current (A)

### Weight and dimension

| Length (mm) | 3000 |
|-------------|------|
| Height (mm) | 23   |
| Width (mm)  | 27   |

## Accessories









6480-10-30 Product Code Right live-end Name 10 Packaging quantity Finishing Black

Product Code 6480-11-30 Left live-end Name Packaging quantity 10

Black Finishing Product Code 6481-00-30 Name Central connector

Packaging quantity 5 Finishing Black Product Code 6453-00-30 Straight connector

Packaging quantity 25 Black Finishing



# Datasheet

|      | Product Code       | 6454-10-30  |
|------|--------------------|---|
|      | Name               | Mechanical joint without electrical contacts                    |
| 50   | Packaging quantity | 25  |
|      | Finishing          | Black   |
| e~~  | Product Code       | 6484-10-30  |
|      | Name               | Inside L joint  |
| 55   | Length (mm)        | 55  |
| 55   | Product Code       | 6484-11-30  |
|      | Name               | Outside L joint   |
| 55   | Length (mm)        | 55  |
|      | Product Code       | 6465-03-31  |
|      | Name               | 150W 220-240V/48VDC DALI electronic transformer, for remote use |
|      | Finishing          | White   |
|      | Product Code       | 81-09000  |
|      | Name               | 100W 230V/48V PWM transformer for remote use                    |
|      |                    |   |
|      | Product Code       | 81-09001  |
|      | Name               | 200W 230V/48V PWM transformer for remote use                    |
|      |                    |   |
|      | Product Code       | 81-90122  |
|      | Name               | 300W 230V/48V PWM transformer for remote use                    |
|      |                    |   |
|      | Product Code       | 81-90089  |
|      | Name               | Bluetooth Casambi dimmer 48V 4 channels                         |
|      |                    |   |
|      | Product Code       | 81-90123  |
|      | Name               | PWM dimmer  |
|      | Draduat Coda       | 01.00124  |
|      | Product Code       | 81-90124  |
|      | Name               | DALI dimmer   |
|      | Product Code       | 81-90128  |
|      | Name               | Bluetooth DALI Controller                                       |
|      | Name               | Bidetouri DALI Controller                                       |
|      | Product Code       | 6457-00-00  |
|      | Name               | Plate 120mm (Compulsory for the connection between tracks)      |
| 120  | Packaging quantity | 1   |
|      | Product Code       | 6461-00-30  |
|      | Name               | Track cover 1000mm  |
| 1000 | Packaging quantity | 10  |
|      |                    |   |



Black



Finishing

## Datasheet



Product Code

Name

Packaging quantity

Finishing

6483-00-30 Dead end 10 Black

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

