


248-230BN-21 RA 17 Dixit LED tiltable 33W 3000K

Design: Studio Tecnico Ivela



IP 20 IK 07



Product Code	Color
248-230BN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Tiltable downlight, designed for the last generation of COB LEDs. It grants a perfect control of the light beam and an excellent colour rendering. LED drivers should be ordered separately, the wattage of the fitting changes depending on the selected driver. Optics for different beams are also available.
Applications	Shops , Retail

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 4250lm 33W 3000K CRI85
Nominal lumens on thermal regime (lm)	4250
LOR	88.7
Delivered lumen (lm)	3770
Watt source (W)	33
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Closing screen	Clear polycarbonate

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Rings	Die-cast aluminium
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Tiltable
Light beam	30°

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C

Weight and dimension

Height (mm)	115
Diameter (mm)	168
Cutout diameter (mm)	155
Recessed depth (mm)	180
Temperature max (°C)	35
Weight (Kg)	2
False ceiling thickness (mm)	1-30

Accessories



Product Code	28-3140-51
Name	Professional optic device S (Including diffuser)
Light beam	17°
Finishing	Mirror metallized



Product Code	28-3138-51
Name	Professional optic device W
Light beam	55°
Finishing	Mirror metallized



Product Code	28-3141-31
Name	Professional optic device XW
Light beam	70°
Finishing	White



Product Code	81-04015
Name	Driver 900mA

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C