
## Lito 12W 3000K CRI85

Design: Enrico Davide Bona & Elisa Nobile





-\\850°

C€ ∰ ∰

IP 65 IK 10



Product Code	Color
11200030	Black
General specifications	
Product type	Outdoor spotlight
Mounting location	Ground/Wall
Indoor/Outdoor light	Outdoor
Description	Exterior projector characterized by shallow lines. It can be mounted on the wall the ground through the proper thermoplastic spike. IP66, high resistant and protected clear thermoplastic screen. Textured thermoplastic cover
Product notes	Bracket in stainless steel.
Applications	Terraces , Residential outdoor areas , Façades , Gardens
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle vers
Lamp description	LED 1800lm 12W 3000K CRI85
Nominal lumens on thermal regime (Im)	1800
LOR	82.5
Delivered lumen (lm)	1486
System wattage (W)	14
Watt source (W)	12
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Closing screen	Clear high resistant thermoplastic material
Physical specifications	
Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Gasket	Silicone
Electrical specifications	
Driver availability	Included
Driver mounting	Integrated
Voltage (V)	230/240
Frequency (Hz)	50/60
Cable gland	M12x1, 5 in nickel-plated brass, including 2mt cable
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Orientation	220° tilting.
Aiming	Tiltable
, annig	

Power tolerance  $\pm\,5\%$  - Luminous flux tolerance  $\pm\,5\%$  - Measurement uncertainty  $\pm\,10\%$  - Ta:  $25^\circ\text{C}$ 

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559

## Datasheet

## Weight and dimension

Product Code

Name IP rating

Length (mm)	161
Height (mm)	120
Width (mm)	155
Weight (Kg)	1.1
Accessories	
Product Code	163400
Name	Stainless steel bracket 250 mm
Length (mm)	250
Name Length (mm)	

84108

IP 68

IP 68 rated cable connector



Power tolerance  $\pm~5\%$  - Luminous flux tolerance  $\pm~5\%$  - Measurement uncertainty  $\pm~10\%$  - Ta:  $25^\circ\text{C}$ 



elcomledcomponents.com info@elcomsrl.net +39 030 6830559