


Stilled 3W 3000K CRI80

Design: Studio Tecnico Ivela



IP 68 3mt IK 08



Product Code	Color
--------------	-------

1583180	
On demand	Yes

General specifications

Product type	Outdoor recessed
Mounting type	Wall - recessed
Mounting location	Wall
Indoor/Outdoor light	Outdoor
Description	Outdoor and indoor recessed LED fitting. Constant current Led driver (cod. 81-04020). Recessed housing included in the fitting.
Applications	Walls , Scenographic solutions , Pedestrian areas , Walkways , Footpaths , Exit ways

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 300lm 3W 3000K CRI80
Nominal lumens on thermal regime (lm)	300
Watt source (W)	3
Color temperature (K)	3000
CRI	CRI 80
Lamp type	LED
Photobiological risk group	RG1
Diffuser	Screen in clear polycarbonate shockproof, hard-wearing

Physical specifications

Body	Inner and recessed housing in high resistant technopolymer
Mechanical load (kg)	1000
Gasket	Double EPDM
Screws	Stainless steel
Frame	Stainless steel

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Cable gland	PG7 for through-wiring

Optical specifications

Light distribution	Asymmetric
Emission	Direct
Aiming	Fixed

Weight and dimension

Length (mm)	184
Width (mm)	60
Recessed depth (mm)	55
Temperature max (°C)	55
Weight (Kg)	0.3

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C

Accessories



Product Code 84108
Name IP 68 rated cable connector
IP rating IP 68



Product Code 160821
Name 10mt Supply cable coil, H05RN-F 2x1 mm²



Product Code 81-04020
Name Driver 350mA Max 4 fittings

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C