## AP Line 30W 3000K CRI85

Design: Enrico Davide Bona & Elisa Nobile









Product Code	Color
3748-01	Mat white
General specifications	
Mounting type	Wall - surface
Mounting location	Wall
Description	Wall light for indirect lighting with a geometric and sober design, for LED COI sources of the last generation. The diffuser provides a uniform light distribution an high visual comfort.
Applications	Entrances , Corridors , Hospitality , Residential
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle version
Lamp description	LED 2800lm 30W 3000K CRI85
Nominal lumens on thermal regime (Im)	2800
LOR	76
Delivered lumen (lm)	2128
System wattage (W)	34,6
Watt source (W)	30
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Diffuser	Opal polycarbonate with high light-diffusion capacity
Physical specifications	
Body	Body and bracket in die-cast aluminium
Finishing	Polyester painted
Thermal dissipation	Passive
Electrical specifications	
Voltage (V)	220/240
Frequency (Hz)	50/60
Optical specifications	
Light distribution	Symmetric
Emission	Uplight
Light beam	110°
Weight and dimension	
Length (mm)	205
Height (mm)	50
Width (mm)	350
Weight (Kg)	1.8

Power tolerance  $\pm$  5% - Luminous flux tolerance  $\pm$  5% - Measurement uncertainty  $\pm$  10% - Ta: 25°C

elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559