


## 776-269BX-21 Microperfetto LKM DALI Large with lens 29W 3000K CRI90 DALI 30°

Design:



IP 20



Product Code	Color
776-269BX-21	Mat white
On demand	Yes
General specifications	
Product type	Track lights
Mounting type	LKM DALI dimmable track
Indoor/Outdoor light	Indoor
Description	Spotlight for dimmable tracks LKM DALI with proper adapter, specially developed for high efficiency COB LEDs. It is equipped with a DALI driver. It's equipped with silicon lens, integrated black snoot and solite.
Applications	Showrooms , Retail , Residential , Museums , Hospitality
Lighting specifications	
<b>i</b> Stated L.O.R. and delivered lumens values are related to standard beam angle versions	
Lamp description	LED 3100lm 29W 3000K CRI90
Nominal lumens on thermal regime (lm)	3100
LOR	85
Delivered lumen (lm)	2635
System wattage (W)	32,8
Watt source (W)	29
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Physical specifications	
Optic device	Silicone lens
Electrical specifications	
Driver type	DALI
Driver availability	Included
Driver mounting	Integrated
Dimmable	DALI dimmable
Voltage (V)	220/240
Frequency (Hz)	50/60
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Light beam	30° Lens
Weight and dimension	
Length (mm)	110
Width (mm)	260
Diameter (mm)	61

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C

ELCOM Srl  
MEMBER OF **STARLIGHT**  
Via Ugo la Malfia 5  
25030 Castel Mella (BS) - ITALY

**elcom**

elcomledcomponents.com  
info@elcomsrl.net  
+39 030 6830559