


775-169B-16 Microperfetto

Large LKM DALI zoom

18,5W 3000K CRI90

Design: Ivela Design Team



IP 20

Product Code	Color
775-169B-16	Black
On demand	Yes

General specifications

Product type	Track lights
Mounting type	LKM DALI dimmable track
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Spotlight for dimmable tracks LKM DALI with proper adapter, specially developed for high efficiency COB LEDs. It is equipped with a DALI driver. It's equipped with zoom lens in PMMA and prismatic spread lens, seven positions adjustable and with a spotlight range from 13° to 47°, and integrated black snoot.
Applications	Showrooms , Retail , Residential , Museums , Hospitality

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1760lm 18,5W 3000K CRI90
Nominal lumens on thermal regime (lm)	1760
LOR	67
Delivered lumen (lm)	1174
System wattage (W)	20,5
Watt source (W)	18.5
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000

Physical specifications

Body	Body and gear box in die-cast aluminium
Finishing	Polyester painted
Optic device	PMMA zoom lens
Thermal dissipation	Passive

Electrical specifications

Driver type	DALI
Driver availability	Included
Driver mounting	Integrated
Dimmable	DALI dimmable
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Light beam	13° to 47°

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Weight and dimension

Length (mm)	110
Width (mm)	260
Diameter (mm)	61

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C