


## 775-169B-21 Microperfetto Large LKM DALI zoom 18,5W 3000K CRI90 DALI

Design: Ivela Design Team



IP 20

| Product Code                          | Color   |
|---------------------------------------|---|
| 775-169B-21                           | Mat white   |
| On demand                             | Yes   |
| General specifications                |   |
| Product type                          | Track lights  |
| Mounting type                         | LKM DALI dimmable track   |
| Mounting location                     | Ceiling   |
| Indoor/Outdoor light                  | Indoor  |
| Description                           | Spotlight for dimmable tracks LKM DALI with proper adapter, specially developed for high efficiency COB LEDs. It is equipped with a DALI driver. It's equipped with zoom lens in PMMA and prismatic spread lens, seven positions adjustable and with a spotlight range from 13° to 47°, and integrated black snoot. |
| Applications                          | Showrooms , Retail , Residential , Museums , Hospitality  |
| Lighting specifications               |   |
| Lamp description                      | LED 1760lm 18,5W 3000K CRI90  |
| Nominal lumens on thermal regime (lm) | 1760  |
| LOR                                   | 67  |
| Delivered lumen (lm)                  | 1174  |
| System wattage (W)                    | 20,5  |
| Watt source (W)                       | 18.5  |
| Color temperature (K)                 | 3000  |
| CRI                                   | CRI 90  |
| Lamp type                             | COB LED   |
| Average lamp life (h)                 | L80B10 50.000   |
| Physical specifications               |   |
| Body                                  | Body and gear box in die-cast aluminium   |
| Finishing                             | Polyester painted   |
| Optic device                          | PMMA zoom lens  |
| Thermal dissipation                   | Passive   |
| Electrical specifications             |   |
| Driver type                           | DALI  |
| Driver availability                   | Included  |
| Driver mounting                       | Integrated  |
| Dimmable                              | DALI dimmable   |
| Voltage (V)                           | 220/240   |
| Frequency (Hz)                        | 50/60   |
| Optical specifications                |   |
| Light distribution                    | Symmetric   |
| Emission                              | Direct  |
| Light beam                            | 13° to 47°  |

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

## Weight and dimension

---

|               |     |
|---------------|-----|
| Length (mm)   | 110 |
| Width (mm)    | 260 |
| Diameter (mm) | 61  |

---

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C