


## 770-069BZ-21 Perfetto Puro 32W 3000K CRI90 17°

Design: Ivela Design Team



IP 20



| Product Code | Color     |
|--------------|-----------|
| 770-069BZ-21 | Mat white |

### General specifications

|                      |  |
|----------------------|--|
| Product type         | Track lights   |
| Mounting type        | LKM 3-phase track  |
| Mounting location    | Ceiling  |
| Indoor/Outdoor light | Indoor   |
| Description          | Track light for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available. |

Applications Museums , Shops , Showrooms , Retail

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

|                                       |                            |
|---------------------------------------|----------------------------|
| Lamp description                      | LED 3830lm 32W 3000K CRI90 |
| Nominal lumens on thermal regime (lm) | 3830                       |
| LOR                                   | 89                         |
| Delivered lumen (lm)                  | 3409                       |
| System wattage (W)                    | 35,7                       |
| Watt source (W)                       | 32                         |
| Color temperature (K)                 | 3000                       |
| CRI                                   | CRI 90                     |
| Lamp type                             | COB LED                    |
| Average lamp life (h)                 | L90B50 50.000              |

### Physical specifications

|                     |  |
|---------------------|--|
| Body                | Die-cast aluminium                       |
| Finishing           | Polyester painted                        |
| Optic device        | Mirror-metallized thermoplastic material |
| Thermal dissipation | Passive                                  |

### Electrical specifications

|                     |            |
|---------------------|------------|
| Driver availability | Included   |
| Driver mounting     | Integrated |
| Voltage (V)         | 220/240    |
| Frequency (Hz)      | 50/60      |

### Optical specifications

|                    |  |
|--------------------|--|
| Light distribution | Symmetric  |
| Emission           | Direct   |
| Orientation        | It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. |
| Light beam         | 17°  |

### Weight and dimension

|               |     |
|---------------|-----|
| Length (mm)   | 92  |
| Width (mm)    | 225 |
| Diameter (mm) | 84  |
| Weight (Kg)   | 0.9 |

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

## Accessories

---



|              |            |
|--------------|------------|
| Product Code | 28-3957-30 |
| Name         | Snoot      |



|              |  |
|--------------|--|
| Product Code | 28-3959-30                                       |
| Name         | Honeycomb, to be used with snoot code 28-3957-30 |

---

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C