


770-069CX-16 Perfetto Puro 32W 2700K CRI90 30°

Design:



IP 20



| Product Code | Color |
|--------------|-------|
| 770-069CX-16 | Black |

General specifications

| | |
|----------------------|--|
| Product type | Track lights |
| Mounting type | LKM 3-phase track |
| Indoor/Outdoor light | Indoor |
| Description | Track light for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available. |

| | |
|--------------|--------------------------------------|
| Applications | Museums , Shops , Showrooms , Retail |
|--------------|--------------------------------------|

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

| | |
|----------------------|----------------------------|
| Lamp description | LED 4400lm 32W 2700K CRI90 |
| LOR | 89 |
| Delivered lumen (lm) | 3273 |
| System wattage (W) | 35,7 |

Physical specifications

| | |
|--------------|--|
| Optic device | Mirror-metallized thermoplastic material |
|--------------|--|

Electrical specifications

| | |
|---------------------|------------|
| Driver availability | Included |
| Driver mounting | Integrated |
| Voltage (V) | 220/240 |
| Frequency (Hz) | 50/60 |

Optical specifications

| | |
|--------------------|--|
| Light distribution | Symmetric |
| Emission | Direct |
| Orientation | It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. |
| Light beam | 30° |

Weight and dimension

| | |
|---------------|-----|
| Length (mm) | 92 |
| Width (mm) | 225 |
| Diameter (mm) | 84 |
| Weight (Kg) | 0.9 |

Accessories

| | |
|--------------|------------|
| Product Code | 28-3957-30 |
| Name | Snoot |

| | |
|--------------|--|
| Product Code | 28-3959-30 |
| Name | Honeycomb, to be used with snoot code 28-3957-30 |

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C

ELCOM Srl
MEMBER OF **STARLIGHT**
Via Ugo la Malfia 5
25030 Castel Mella (BS) - ITALY

elcom

elcomledcomponents.com
info@elcomsrl.net
+39 030 6830559