
770-269AT-21 Perfetto Puro 37W 4000K CRI90 70°





IP 20



	Color
770-269AT-21	Mat white
General specifications	
Product type	Track lights
Mounting type	LKM 3-phase track
Indoor/Outdoor light	Indoor
Description	Track light for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.
Applications	Museums , Retail , Shops , Showrooms
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle versions
Lamp description	LED 5000lm 37W 4000K CRI90
Nominal lumens on thermal regime (Im)	5000
LOR	89
Delivered lumen (Im)	4425
System wattage (W)	35,7
Watt source (W)	37
Color temperature (K)	4000
CRI	CRI 90
Lamp type	COB LED
Lamp type	
Average lamp life (h)	L80B10 50.000
Average lamp life (h)	L80B10 50.000
	L80B10 50.000 Mirror-metallized thermoplastic material
Average lamp life (h) Physical specifications Optic device	
Average lamp life (h) Physical specifications	
Average lamp life (h) Physical specifications Optic device Electrical specifications	Mirror-metallized thermoplastic material
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability	Mirror-metallized thermoplastic material
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting	Mirror-metallized thermoplastic material Included Integrated
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V)	Mirror-metallized thermoplastic material Included Integrated 220/240
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications	Mirror-metallized thermoplastic material Included Integrated 220/240
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz)	Mirror-metallized thermoplastic material Included Integrated 220/240 50/60
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution	Mirror-metallized thermoplastic material Included Integrated 220/240 50/60 Symmetric
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission	Mirror-metallized thermoplastic material Included Integrated 220/240 50/60 Symmetric Direct
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation Light beam	Mirror-metallized thermoplastic material Included Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation Light beam	Mirror-metallized thermoplastic material Included Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation Light beam Weight and dimension	Mirror-metallized thermoplastic material Included Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. 70°
Average lamp life (h) Physical specifications Optic device Electrical specifications Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation Light beam Weight and dimension Length (mm)	Mirror-metallized thermoplastic material Included Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. 70°

Power tolerance \pm 5% - Luminous flux tolerance \pm 5% - Measurement uncertainty \pm 10% - Ta: 25°C

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559



Accessories

Product Code

Product Code Name

Name

28-3957-30 Snoot

28-3959-30 Honeycomb, to be used with snoot code 28-3957-30

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY



elcomledcomponents.com info@elcomsrl.net +39 030 6830559