
770-269BV-21 Perfetto Puro 37W 3000K CRI90 55°

Design:



| E | | |
|---|---|--|
| | | |
| | 1 | |
| | | |
| | | |
| | | |
| | | |













IP 20



| _ | _ | _ | |
|---|---|---|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Applications

| Product Code | Color |
|------------------------|--|
| 770-269BV-21 | Mat white |
| General specifications | |
| Product type | Track lights |
| Mounting type | LKM 3-phase track |
| Indoor/Outdoor light | Indoor |
| Description | Track light for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available. |

| Lighting specifications | i Stated L.O.R. and delivered lumens values are related to standard beam angle vers | |
|-------------------------|---|--|
| Lamp description | Led 4400lm 37W 3000K | |

Museums , Shops , Showrooms , Retail

| Nominal lumens on thermal regime (Im) | 3916 |
|---------------------------------------|---------------|
| LOR | 89 |
| Delivered lumen (Im) | 3916 |
| System wattage (W) | 35,7 |
| Watt source (W) | 37 |
| Color temperature (K) | 3000 |
| CRI | CRI 90 |
| Average lamp life (h) | L80B10 50.000 |
| | |

Physical specifications

Electrical specifications

| Driver availability | Included |
|---------------------|------------|
| Driver mounting | Integrated |
| Voltage (V) | 220/240 |
| Frequency (Hz) | 50/60 |

Optical specifications

| Light distribution | Symmetric |
|--------------------|--|
| Emission | Direct |
| Orientation | It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. |
| Light beam | 55° |

Weight and dimension

| Length (mm) | 92 |
|---------------|-----|
| Width (mm) | 225 |
| Diameter (mm) | 84 |
| Weight (Kg) | 0.9 |



Datasheet

Accessories





Product Code 28-3957-30
Name Snoot

Product Code 28-3959-30

Name Honeycomb, to be used with snoot code 28-3957-30

Power tolerance \pm 5% - Luminous flux tolerance \pm 5% - Measurement uncertainty \pm 10% - Ta: 25°C

