
770-269BZ-21 Perfetto Puro 37W 3000K CRI90 17°





IP 20



	Color
770-269BZ-21	Mat white
General specifications	
Product type	Track lights
Mounting type	LKM 3-phase track
Indoor/Outdoor light	Indoor
Description	Track light for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.
Applications	Museums , Shops , Showrooms , Retail
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle version
Lamp description	Led 4400lm 37W 3000K
Nominal lumens on thermal regime (Im)	3916
LOR	89
Delivered lumen (lm)	3916
System wattage (W)	35,7
Watt source (W)	37
Color temperature (K)	3000
CRI	CRI 90
Average lamp life (h)	L80B10 50.000
Physical specifications	
Optic device	Mirror-metallized thermoplastic material
Electrical specifications	
Electrical specifications Driver availability	Included
-	Included
Driver availability	
Driver availability Driver mounting	Integrated
Driver availability Driver mounting Voltage (V)	Integrated 220/240
Driver availability Driver mounting Voltage (V) Frequency (Hz)	Integrated 220/240
Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications	Integrated 220/240 50/60
Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution	Integrated 220/240 50/60 Symmetric
Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission	Integrated 220/240 50/60 Symmetric Direct
Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation	Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation Light beam	Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation Light beam Weight and dimension Length (mm)	Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. 17°
Driver availability Driver mounting Voltage (V) Frequency (Hz) Optical specifications Light distribution Emission Orientation Light beam Weight and dimension	Integrated 220/240 50/60 Symmetric Direct It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. 17°

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559



Accessories

Product Code

Product Code Name

Name

28-3957-30 Snoot

28-3959-30 Honeycomb, to be used with snoot code 28-3957-30

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY



elcomledcomponents.com info@elcomsrl.net +39 030 6830559