


## 770-269CT-16 Perfetto Puro 37W 2700K CRI90 70°

Design:



IP 20



| Product Code | Color |
|--------------|-------|
| 770-269CT-16 | Black |

### General specifications

|                      |                                                                                                                                                            |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product type         | Track lights                                                                                                                                               |
| Mounting type        | LKM 3-phase track                                                                                                                                          |
| Indoor/Outdoor light | Indoor                                                                                                                                                     |
| Description          | Track light for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available. |
| Applications         | Museums , Shops , Showrooms , Retail                                                                                                                       |

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

|                      |      |
|----------------------|------|
| LOR                  | 89   |
| Delivered lumen (lm) | 3759 |
| System wattage (W)   | 35,7 |

### Physical specifications

|              |                                          |
|--------------|------------------------------------------|
| Optic device | Mirror-metallized thermoplastic material |
|--------------|------------------------------------------|

### Electrical specifications

|                     |            |
|---------------------|------------|
| Driver availability | Included   |
| Driver mounting     | Integrated |
| Voltage (V)         | 220/240    |
| Frequency (Hz)      | 50/60      |

### Optical specifications

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Light distribution | Symmetric                                                                      |
| Emission           | Direct                                                                         |
| Orientation        | It can rotate up to 355° around the vertical axis and pivot up to 90° upwards. |
| Light beam         | 70°                                                                            |

### Weight and dimension

|               |     |
|---------------|-----|
| Length (mm)   | 92  |
| Width (mm)    | 225 |
| Diameter (mm) | 84  |
| Weight (Kg)   | 0.9 |

### Accessories

|              |                                                  |
|--------------|--------------------------------------------------|
| Product Code | 28-3957-30                                       |
| Name         | Snoot                                            |
| Product Code | 28-3959-30                                       |
| Name         | Honeycomb, to be used with snoot code 28-3957-30 |



Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C

ELCOM Srl  
MEMBER OF **STARLIGHT**  
Via Ugo la Malfia 5  
25030 Castel Mella (BS) - ITALY

**elcom**

elcomledcomponents.com  
info@elcomsrl.net  
+39 030 6830559