


751-2613BY-21 Perfetto Compact 26W 3000K CRI85 20°

Design: Ivela Design Team



IP 20



Product Code	Color
751-2613BY-21	Mat white
General specifications	
Product type	Track lights
Mounting type	LKM 3-phase track
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Spotlight for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.
Applications	Showrooms , Shops , Retail , Museums
Lighting specifications	
Lamp description	LED 3125lm 26W 3000K CRI85
Nominal lumens on thermal regime (lm)	3125
LOR	72.9
Delivered lumen (lm)	2278
System wattage (W)	28,9
Watt source (W)	26
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16
Physical specifications	
Body	Body and joint in die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive
Electrical specifications	
Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60
Optical specifications	
Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Light beam	20°

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Weight and dimension

Length (mm)	175
Height (mm)	232
Diameter (mm)	67
Weight (Kg)	1

Accessories



Product Code	28-9004-30
Name	Snoot



Product Code	28-4080-30
Name	Honeycomb, to be used with snoot code 28-9004-30



Product Code	28-3905-47
Name	Closing screen in clear thermoplastic

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C