


751-3613BW-16 Perfetto Compact 30W 3000K CRI85 42°

Design: Ivela Design Team



IP 20



Product Code	Color
751-3613BW-16	Black

General specifications

Product type	Track lights
Mounting type	LKM 3-phase track
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Spotlight for LKM 3-phase electrified tracks, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.
Applications	Showrooms , Shops , Retail , Museums

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 3500lm 30W 3000K CRI85
Nominal lumens on thermal regime (lm)	3500
LOR	72.9
Delivered lumen (lm)	2552
System wattage (W)	32,5
Watt source (W)	30
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16

Physical specifications

Body	Body and joint in die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Light beam	42°

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Weight and dimension

Length (mm)	175
Height (mm)	232
Diameter (mm)	67
Weight (Kg)	1

Accessories



Product Code	28-9004-30
Name	Snoot



Product Code	28-4080-30
Name	Honeycomb, to be used with snoot code 28-9004-30



Product Code	28-3905-47
Name	Closing screen in clear thermoplastic

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C