



710-369B-21 Perfetto Puro
LKM DALI Zoom 29W
3000K CRI90

Design:



IP 20



Product Code	Color
--------------	-------

710-369B-21	Mat white
-------------	-----------

General specifications

Product type	Track lights
Mounting type	LKM 3-phase track DALI
Indoor/Outdoor light	Indoor
Description	Track light for LKM DALI 3-phase electrified tracks, specially developed for high efficiency COB LEDs. The rotation of the internal snoot modifies the beam angle from 16° to 45°. The group of switches Dip Switch allows the selection of different steps of wattage (13-15-17-19-21-23-25-27-29W)

Applications	Museums , Shops , Showrooms , Retail
--------------	--------------------------------------

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 3651lm 29W 3000K CRI90
Nominal lumens on thermal regime (lm)	3651
LOR	83
Delivered lumen (lm)	3030
Watt source (W)	29
Color temperature (K)	3000
CRI	CRI 90
Lamp type	LED stripe
Average lamp life (h)	L80B10 50.000

Physical specifications

Optic device	PMMA lens
--------------	-----------

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Light beam	16° to 45°

Weight and dimension

Length (mm)	131
Width (mm)	213
Diameter (mm)	84
Weight (Kg)	1.2

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C

ELCOM Srl
MEMBER OF **STARLIGHT**
Via Ugo la Malfia 5
25030 Castel Mella (BS) - ITALY

elcom

elcomledcomponents.com
info@elcomsrl.net
+39 030 6830559