## 256-200AN-21 - RA 11 Dixit LED tiltable 4000K - 26W









Product Code	Color	
256-200AN-21	Mat white	
General specifications		
Product type	Downlights	
Mounting type	Ceiling - recessed	
Mounting location	Ceiling	
Indoor/Outdoor light	Indoor	
Description	Tiltable downlight for diffused lighting designed for the last generation of COB LED with a shallow depth. LED drivers should be ordered separately, the wattage of th fittings changes depending on the selected driver. Protection rating IP20. Low glau levels UGR < 19 (Unified Glare Rating).	
Applications	Shops , Retail , Offices	
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle versions	
Lamp description	LED 3200lm 26W 4000K CRI85	
Nominal lumens on thermal regime (Im)	3200	
LOR	89	
Delivered lumen (lm)	2848	
Watt source (W)	26	
Color temperature (K)	4000	
CRI	CRI 85	
Lamp type	COB LED	
Average lamp life (h)	L80B10 50.000	
Photobiological risk group	RG1	
Unified Glare Rating (U.G.R. <)	19	
Closing screen	Clear polycarbonate	
Physical specifications		
Body	Die-cast aluminium	
Finishing	Polyester painted	
Optic device	Mirror-metallized thermoplastic material	
Rings	Die-cast aluminium	
Thermal dissipation	Passive	
Electrical specifications		
Driver availability	Separate	
Driver mounting	Separate	
Dimmable	Dimmable on the mains / DALI / 1-10V / Push	
Optical specifications		
Light distribution	Symmetric	
Emission	Direct	
Aiming	Tiltable	
Light beam	55°	

Power tolerance  $\pm~5\%$  - Luminous flux tolerance  $\pm~5\%$  - Measurement uncertainty  $\pm~10\%$  - Ta:  $25^\circ\text{C}$ 

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559

## Datasheet

## Weight and dimension

Height (mm)	79
Diameter (mm)	125
Cutout diameter (mm)	116
Recessed depth (mm)	79
Weight (Kg)	0.7
False ceiling thickness (mm)	1-30

Professional optic device S (Including diffuser)

28-3140-51

Mirror metallized

Professional optic device M

28-3142-51

18°

## Accessories

Product Code

Light beam Finishing

Product Code

Name

Name









-

K.

	•
Light beam	30°
Finishing	Mirror metallized
Product Code	28-3141-31
Name	Professional optic device XW
Light beam	70°
Finishing	White
Draduct Cada	20,4010,20
Product Code	28-4019-30
Name	Honeycomb
Finishing	Black painted
Product Code	81-04012
Name	Driver 700mA
Product Code	81-04044
Name	Driver 700mA Dimmable on the mains
Product Code	81-02413
Name	Driver 700 mA Dimmable DALI
Product Code	81-04066
Name	Driver 700mA dimmable 1-10V

Power tolerance  $\pm~5\%$  - Luminous flux tolerance  $\pm~5\%$  - Measurement uncertainty  $\pm~10\%$  - Ta:  $25^\circ\text{C}$ 

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559