
255-200AN-21 - RA 11 Dixit

LED 4000K - 18W

Design:

















Product Code Color

255-200AN-21 Mat white

General specifications

Downlights Product type Ceiling - recessed Mounting type Mounting location Ceiling Indoor/Outdoor light Indoor

Description Fixed downlight for diffused lighting designed for the last generation of COB LEDs, with a shallow depth. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP43. Low glare

levels UGR < 19 (Unified Glare Rating).

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Shops, Retail, Offices Applications

Lighting specifications

LED 2450lm 18W 4000K CRI85

Lamp description Nominal lumens on thermal regime (Im) 2450 LOR 89 2180 Delivered lumen (lm) Watt source (W) 18 Color temperature (K) 4000 CRI **CRI 85** COB LED Lamp type L80B10 50.000 Average lamp life (h)

RG1 Photobiological risk group Unified Glare Rating (U.G.R. <)

Closing screen Clear polycarbonate

Physical specifications

Body Die-cast aluminium Finishing Polyester painted

Optic device Mirror-metallized thermoplastic material

Die-cast aluminium Rings

Thermal dissipation Passive

Electrical specifications

Driver availability Separate Driver mounting Separate

Optical specifications

Symmetric Light distribution Direct Emission Aiming Fixed Light beam 55°



Weight and dimension

Height (mm)	70
Diameter (mm)	110
Cutout diameter (mm)	100
Recessed depth (mm)	70
Weight (Kg)	0.6
False ceiling thickness (mm)	1-30

Accessories

Product Code 28-3140-51

Name Professional optic device S (Including diffuser)

Light beam 18

Finishing Mirror metallized

Product Code 28-3142-51

Name Professional optic device M

Light beam 30°

Finishing Mirror metallized

Product Code 28-3141-31

Name Professional optic device XW

Light beam 70°
Finishing White

Product Code 28-4019-30
Name Honeycomb
Finishing Black painted

 Product Code
 81-04011

 Name
 Driver 500mA

Product Code 81-04002

Name Driver 500mA DALI dimmable



