255-200AN-21 - RA 11 Dixit LED 4000K - 26W

Design:







Product Code	Color Mat white	
255-200AN-21		
General specifications		
Product type	Downlights	
Mounting type	Ceiling - recessed	
Mounting location	Ceiling	
Indoor/Outdoor light	Indoor	
Description	Fixed downlight for diffused lighting designed for the last generation of COB LEDs, with a shallow depth. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP43. Low glare levels UGR < 19 (Unified Glare Rating).	
Applications	Shops , Retail , Offices	
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle version	
Lamp description	LED 3200lm 26W 4000K CRI85 L90B50 50.000 h	
Nominal lumens on thermal regime (Im)	3200	
LOR	89	
Delivered lumen (lm)	2844	
Watt source (W)	26	
Color temperature (K)	4000	
CRI	CRI 85	
Lamp type	COB LED	
Average lamp life (h)	L90B50 50.000	
Photobiological risk group	RG1	
Unified Glare Rating (U.G.R. <)	19	
Closing screen	Clear polycarbonate	
Physical specifications		
Body	Die-cast aluminium	
Finishing	Polyester painted	
Optic device	Mirror-metallized thermoplastic material	
Rings	Die-cast aluminium	
Thermal dissipation	Passive	
Electrical specifications		
Driver availability	Separate	
Driver mounting	Separate	
Dimmable	Dimmable on the mains / DALI / 1-10V / Push	
Optical specifications		
Light distribution	Symmetric	
Emission	Direct	
Aiming	Fixed	
Light beam	55°	

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559

Datasheet

Weight and dimension

Height (mm)	70
Diameter (mm)	110
Cutout diameter (mm)	100
Recessed depth (mm)	70
Weight (Kg)	0.6
False ceiling thickness (mm)	1-30

Professional optic device S (Including diffuser)

28-3140-51

Mirror metallized

28-3142-51

18°

Accessories

Product Code

Light beam Finishing

Product Code

Name









7

E.

T Toddet Gode	20 0142 01
Name	Professional optic device M
Light beam	30°
Finishing	Mirror metallized
Product Code	28-3141-31
Name	Professional optic device XW
Light beam	70°
•	White
Finishing	white
Product Code	28-4019-30
Name	Honeycomb
Finishing	Black painted
Product Code	81-04012
Name	Driver 700mA
Product Code	81-04044
Name	Driver 700mA Dimmable on the mains
Product Code	81-02413
Name	Driver 700 mA Dimmable DALI
Product Code	81-04066
Name	Driver 700mA dimmable 1-10V

Power tolerance \pm 5% - Luminous flux tolerance \pm 5% - Measurement uncertainty \pm 10% - Ta: 25°C

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559