259-200BN-21 - RA 11 Q Dixit LED 3000K - 12W









Product Code	Color Mat white	
259-200BN-21		
General specifications		
Product type	Downlights	
Mounting type	Ceiling - recessed	
Mounting location	Ceiling	
Indoor/Outdoor light	Indoor	
Description	Fixed downlight designed for the last generation of COB LEDs, with a shallow depth. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP43. Low glare levels UGR < 19 (Unified Glare Rating).	
Applications	Shops , Retail , Offices	
Lighting specifications	i Stated L.O.R. and delivered lumens values are related to standard beam angle version	
Lamp description	LED 1700lm 12W 3000K CRI85	
Nominal lumens on thermal regime (Im)	1700	
LOR	89	
Delivered lumen (lm)	1513	
Watt source (W)	12	
Color temperature (K)	3000	
CRI	CRI 85	
Lamp type	COB LED	
Average lamp life (h)	L80B10 50.000	
Photobiological risk group	RG1	
Unified Glare Rating (U.G.R. <)	19	
Unified Glare Rating notes	except for 70° optic	
Closing screen	Clear polycarbonate	
Physical specifications		
Body	Die-cast aluminium	
Finishing	Polyester painted	
Optic device	Mirror-metallized thermoplastic material	
Rings	Die-cast aluminium	
Thermal dissipation	Passive	
Electrical specifications		
Driver availability	Separate	
Driver mounting	Separate	
Dimmable	Dimmable on the mains / DALI dimmable	
Optical specifications		
Light distribution	Symmetric	
Emission	Direct	
Aiming	Fixed	
Light beam	55°	
Optical notes	12°, 30° (mirror metallized), 70° (white) optics are available on demand.	

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: $25^{\circ}C$

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY

elcom

elcomledcomponents.com info@elcomsrl.net +39 030 6830559

Datasheet

Weight and dimension

Length (mm)	117
Height (mm)	73
Width (mm)	117
Cutout diameter (mm)	100
Recessed depth (mm)	73
Weight (Kg)	0.7
False ceiling thickness (mm)	1-30

Accessories









Product Code	28-3140-51
Name	Professional optic device S (Including diffuser)
Light beam	12°
Finishing	Mirror metallized
Product Code	28-3142-51
Name	Professional optic device M
Light beam	30°
Finishing	Mirror metallized
Product Code	28-3141-31
	Professional optic device XW
	•
Light beam	70°
Finishing	White
Product Code	28-4019-30
Name	Honeycomb
Finishing	Black painted
Product Code	81-04010
Name	Driver 350mA dimmable on the mains
Description	Max 1 fitting
Product Code	81-04003
Name	Driver 350mA DALI dimmable
	Name Light beam Finishing Product Code Name Light beam Finishing Product Code Name Light beam Finishing Product Code Name Finishing

Power tolerance $\pm\,5\%$ - Luminous flux tolerance $\pm\,5\%$ - Measurement uncertainty $\pm\,10\%$ - Ta: 25°C

ELCOM SrI MEMBER OF **STARLIGHT** Via Ugo la Malfia 5 25030 Castel Mella (BS) - ITALY



elcomledcomponents.com info@elcomsrl.net +39 030 6830559