


## 259-200BN-21 - RA 11 Q Dixit LED 3000K - 26W

Design:



IP 43 IK 09



Product Code	Color
259-200BN-21	Mat white

### General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Fixed downlight designed for the last generation of COB LEDs, with a shallow depth. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP43. Low glare levels UGR < 19 (Unified Glare Rating).
Applications	Shops , Retail , Offices

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 3100lm 26W 3000K CRI85 L90B50 50.000 h
Nominal lumens on thermal regime (lm)	3100
LOR	89
Delivered lumen (lm)	2759
Watt source (W)	26
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L90B50 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	19
Unified Glare Rating notes	except for 70° optic
Closing screen	Clear polycarbonate

### Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Rings	Die-cast aluminium
Thermal dissipation	Passive

### Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI / 1-10V / Push

### Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	55°
Optical notes	12°, 30° (mirror metallized), 70° (white) optics are available on demand.

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

## Weight and dimension

Length (mm)	117
Height (mm)	73
Width (mm)	117
Cutout diameter (mm)	100
Recessed depth (mm)	73
Weight (Kg)	0.7
False ceiling thickness (mm)	1-30

## Accessories



Product Code	28-3140-51
Name	Professional optic device S (Including diffuser)
Light beam	12°
Finishing	Mirror metallized



Product Code	28-3142-51
Name	Professional optic device M
Light beam	30°
Finishing	Mirror metallized



Product Code	28-3141-31
Name	Professional optic device XW
Light beam	70°
Finishing	White



Product Code	28-4019-30
Name	Honeycomb
Finishing	Black painted



Product Code	81-04012
Name	Driver 700mA



Product Code	81-04044
Name	Driver 700mA Dimmable on the mains



Product Code	81-02413
Name	Driver 700 mA Dimmable DALI



Product Code	81-04066
Name	Driver 700mA dimmable 1-10V

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C