



243-250AN-21 - RA 14 Dixit LED 4000K - 26W

Design: Studio Tecnico Ivela



IP 44 IK 08



Product Code

243-250AN-21

Color

Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Fixed downlight for diffused lighting designed for the last generation of COB LEDs. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP44.

Applications Showrooms , Shops , Retail , Accommodation facilities

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 3500lm 26W 4000K CRI85
Nominal lumens on thermal regime (lm)	3500
LOR	86
Delivered lumen (lm)	3100
Watt source (W)	26
Color temperature (K)	4000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Safety glass	Tempered safety glass 4 mm
Rings	Die-cast aluminium polyester painted
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI / 1-10V / Push

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	60°

Power tolerance \pm 5% - Luminous flux tolerance \pm 5% - Measurement uncertainty \pm 10% - Ta: 25°C

Weight and dimension

Height (mm)	140
Diameter (mm)	140
Cutout diameter (mm)	126
Recessed depth (mm)	150
Weight (Kg)	0.7
False ceiling thickness (mm)	1-30

Accessories



Product Code	98-13380-61
Name	Frosted glass



Product Code	81-04012
Name	Driver 700mA



Product Code	81-04044
Name	Driver 700mA Dimmable on the mains



Product Code	81-02413
Name	Driver 700 mA Dimmable DALI



Product Code	81-04066
Name	Driver 700mA dimmable 1-10V

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C