



## 244-242AN-21 RA 20 Dixit LED 51W 4000K

Design: Studio Tecnico Ivela



IP 44 IK 07



Product Code	Color
244-242AN-21	Mat white

### General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Fixed downlight for diffused lighting, designed for the last generation of COB LEDs, easy to install in false ceilings also with staves from 1 to 30 mm. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP44.
Applications	Showrooms , Shops , Retail , Architectural features , Accommodation facilities

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 6600lm 51W 4000K CRI85
Nominal lumens on thermal regime (lm)	6600
LOR	85.7
Delivered lumen (lm)	5656
Watt source (W)	51
Color temperature (K)	4000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

### Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Safety glass	Tempered safety glass 4 mm
Rings	Die-cast aluminium polyester painted
Thermal dissipation	Passive

### Electrical specifications

Driver availability	Separate
Driver mounting	Separate

### Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	100°

Power tolerance  $\pm$  5% - Luminous flux tolerance  $\pm$  5% - Measurement uncertainty  $\pm$  10% - Ta: 25°C

## Weight and dimension

---

Height (mm)	95
Diameter (mm)	200
Cutout diameter (mm)	185
Recessed depth (mm)	143
Weight (Kg)	1.8
False ceiling thickness (mm)	1-30

## Accessories

---



Product Code	81-04004
Name	Driver 1400mA (max 60W)



Product Code	81-04016
Name	Driver 1400mA (max 60W) Dimmable DALI

---

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C