


## 249-240AN-21 RA 23SP

### Dixit LED 51W 4000K

Design: Studio Tecnico Ivela



IP 44 IK 07



Product Code	Color
249-240AN-21	Mat white

#### General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Professional recessed downlights with fixed optics, providing great lighting performance thanks to the high efficiency COB LEDs of last generation. The RA 23 SP DIXIT LED luminaires, with passive heat dissipation, grant a high luminous density and an excellent colour rendering. They are easy to install in false ceilings from 1 to 30 mm, through specific springs LED drivers should be ordered separately, the wattage of the fittings changes depending on the select driver.

Applications	Showrooms , Shops , Retail , Offices , Conference rooms , Accommodation facilities
--------------	--

#### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 7000lm 51W 4000K CRI85
Nominal lumens on thermal regime (lm)	7000
LOR	85.7
Delivered lumen (lm)	5998
Watt source (W)	51
Color temperature (K)	4000
CRI	CRI 85
Lamp type	COB LED
Photobiological risk group	RG1

#### Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Safety glass	Tempered safety glass 4 mm
Rings	Die-cast aluminium
Thermal dissipation	Passive

#### Electrical specifications

Driver availability	Separate
Driver mounting	Separate

#### Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	100°

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C

### Weight and dimension

Height (mm)	108
Diameter (mm)	235
Cutout diameter (mm)	220
Recessed depth (mm)	155
Weight (Kg)	3.6
False ceiling thickness (mm)	1-30

### Accessories



Product Code	81-04004
Name	Driver 1400mA (max 60W)



Product Code	81-04016
Name	Driver 1400mA (max 60W) Dimmable DALI



Product Code	81-04018
Name	Driver 1400mA (max 100W)

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C