


## 249-250AN-21 RA 23SP Dixit LED 75W 4000K

Design:



IP 44 IK 07



### Product Code

249-250AN-21

### Color

Mat white

### General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Indoor/Outdoor light	Indoor
Description	Professional recessed downlights with fixed optics, providing great lighting performance thanks to the high efficiency COB LEDs of last generation. The RA 23 SP DIXIT LED luminaires, with passive heat dissipation, grant a high luminous density and an excellent colour rendering. They are easy to install in false ceilings from 1 to 30 mm, through specific springs LED drivers should be ordered separately, the wattage of the fittings changes depending on the select driver.

### Applications

Showrooms , Shops , Retail , Offices , Conference rooms , Accommodation facilities

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 9900lm 75W 3000K CRI85
Nominal lumens on thermal regime (lm)	9900
LOR	85.7
Delivered lumen (lm)	8484
Watt source (W)	75
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1

### Physical specifications

Optic device	Mirror-metallized thermoplastic material
Safety glass	Tempered safety glass 4 mm

### Electrical specifications

Driver availability	Separate
Driver mounting	Separate

### Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	100°

### Weight and dimension

Height (mm)	108
Diameter (mm)	235
Cutout diameter (mm)	220
Recessed depth (mm)	155
Weight (Kg)	3.6
False ceiling thickness (mm)	1-30

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

## Accessories

---



Product Code

81-04004

Name

Driver 1400mA (max 60W)



Product Code

81-04016

Name

Driver 1400mA (max 60W) Dimmable DALI



Product Code

81-04018

Name

Driver 1400mA (max 100W)

---

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C