


239-250AN-21 RA 8 Dixit LED tiltable 4000K CRI 80 - 12W

Design:



IP 20 IK 08



Product Code	Color
--------------	-------

239-250AN-21	Mat white
--------------	-----------

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Recessed tiltable downlight, designed for the last generation of COB LEDs. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Low glare level: UGR < 19.
Applications	Showrooms , Shops , Residential , Accommodation facilities

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 1843lm 12W 4000K CRI80
Nominal lumens on thermal regime (lm)	1843
LOR	87.7
Delivered lumen (lm)	1491
Watt source (W)	12
Color temperature (K)	4000
CRI	CRI 80
Average lamp life (h)	L90B50 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	19
Closing screen	Clear polycarbonate

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains / DALI dimmable

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	20°+20° tilting.
Aiming	Tiltable
Light beam	26°
Optical notes	45° (mirror metallized), 65° (white) optics are available on demand.

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Weight and dimension

Height (mm)	82
Diameter (mm)	95
Cutout diameter (mm)	86
Recessed depth (mm)	82
Weight (Kg)	0.4
False ceiling thickness (mm)	1-30

Accessories



Product Code	28-3868-51
Name	Professional optic device W
Light beam	45°
Finishing	Mirror metallized



Product Code	28-3868-31
Name	Professional optic device XW
Light beam	65°
Finishing	White



Product Code	81-04010
Name	Driver 350mA dimmable on the mains
Description	Max 1 fitting



Product Code	81-04003
Name	Driver 350mA DALI dimmable

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C