


238-239BN-21 RA 8 L Dixit LED 26° 3000K CRI90 - 5,5W

Design:



h 50 mm ø 70 mm 0,4 Kg



IP 44 IK 08



Product Code	Color
238-239BN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	Fixed downlight designed for the last generation of COB LEDs, with a shallow depth. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP44. Low glare level: UGR < 15.
Applications	Showrooms , Shops , Residential , Accommodation facilities

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 700lm 8.5W 3000K CRI90
Nominal lumens on thermal regime (lm)	700
LOR	91
Delivered lumen (lm)	638
Watt source (W)	8.5
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	15
Closing screen	Clear polycarbonate

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	Mirror-metallized thermoplastic material
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate
Dimmable	Dimmable on the mains and 1-10V - DALI

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	26°
Optical notes	45° (mirror metallized), 65° (white) optics are available on demand.

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Weight and dimension

Height (mm)	50
Diameter (mm)	80
Cutout diameter (mm)	70
Recessed depth (mm)	50
Weight (Kg)	0.4
False ceiling thickness (mm)	1-30

Accessories



Product Code	28-3868-51
Name	Professional optic device W
Light beam	45°
Finishing	Mirror metallized



Product Code	28-3868-31
Name	Professional optic device XW
Light beam	65°
Finishing	White



Product Code	81-04007
Name	Driver 350mA Dimmable on the mains and 1-10V

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C