


380T 18W 3000K CRI85 Emergency 3h

Design:



IP 65 IK 10

| Product Code | Color |
|--------------|-------|
| 142600 | White |

General specifications

| | |
|----------------------|---|
| Indoor/Outdoor light | Outdoor |
| Description | Outdoor ceiling luminaires ideal for application in residential areas for both indoor and outdoor use. IP65 |
| Applications | Residential areas |

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

| | |
|---------------------------------------|----------------------------|
| Lamp description | LED 2400lm 18W 3000K CRI85 |
| Nominal lumens on thermal regime (lm) | 2400 |
| LOR | 70.9 |
| Delivered lumen (lm) | 1702 |
| System wattage (W) | 23,4 |
| Watt source (W) | 18 |
| Color temperature (K) | 3000 |
| CRI | CRI 85 |
| Lamp type | COB LED |
| Average lamp life (h) | L80B10 50.000 |
| Photobiological risk group | RG1 |
| Diffuser | Polycarbonate |

Electrical specifications

| | |
|---------------------|------------|
| Driver availability | Included |
| Driver mounting | Integrated |

Optical specifications

| | |
|--------------------|-----------|
| Light distribution | Symmetric |
| Emission | Direct |
| Aiming | Fixed |
| Light beam | 110° |

Weight and dimension

| | |
|---------------|-----|
| Height (mm) | 120 |
| Diameter (mm) | 380 |
| Weight (Kg) | 2.7 |

Power tolerance $\pm 5\%$ - Luminous flux tolerance $\pm 5\%$ - Measurement uncertainty $\pm 10\%$ - Ta: 25°C