Perfetto Compact LKM Cut-Phase 18W 4000K CRI85

29°

_					
\Box	00	٩i	a	n	
ν	CC	1	ч	11	

















Product Code	Colo

751-1613AXMD-21 Mat white

General specifications

Applications

Product type Track lights

Mounting type LKM 3-phase track

Indoor/Outdoor light Indoor

Description Spotlight for LKM 3-phase electrified tracks with Cut-Phase power supply, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are

available.

Showrooms , Shops , Retail , Museums

Lighting specifications i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 2710lm 18W 4000K CRI85
Nominal lumens on thermal regime (Im)	2710
LOR	72.9
Delivered lumen (Im)	1750
System wattage (W)	19,4
Watt source (W)	18
Color temperature (K)	4000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Unified Glare Rating (U.G.R. <)	16

Physical specifications

Optic device Mirror-metallized thermoplastic material

Electrical specifications

Driver availability Included
Driver mounting Integrated
Dimmable

Dimmable on the mains

 Voltage (V)
 220/240

 Frequency (Hz)
 50/60

Optical specifications

Light distribution Symmetric
Emission Direct

Orientation It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.

Light beam 29°

Weight and dimension

 Length (mm)
 175

 Height (mm)
 232

 Diameter (mm)
 67

 Weight (Kg)
 1

Power tolerance \pm 5% - Luminous flux tolerance \pm 5% - Measurement uncertainty \pm 10% - Ta: 25°C



Datasheet

Accessories











Product Code 28-9004-30 Name Snoot

28-4080-30 Product Code

Name Honeycomb, to be used with snoot code 28-9004-30

28-3905-47 Product Code

Name Closing screen in clear thermoplastic

Product Code 14768

Adapter for plasterboard to be used with cod.14769 Name

14769 Product Code

Ceiling Adapter Name