Datasheet

Perfetto Compact LKM Cut-Phase 18W 3000K CRI85 20°

Design:

CE ⊕ ⧉ 850°

⏚

IP 20

Product Code	Color
751-1613BYMD-21	Mat white

General specifications

Product type	Track lights
Mounting type	LKM 3-phase track
Indoor/Outdoor light	Indoor
Description	Spotlight for LKM 3-phase electrified tracks with Cut-Phase power supply, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.
Applications	Showrooms , Shops , Retail , Museums

Lighting specifications

ℹ️ **Stated L.O.R. and delivered lumens values are related to standard beam angle versions**

Lamp description	LED 2400lm 18W 3000K CRI85
Nominal lumens on thermal regime (lm)	2400
LOR	72.9
Delivered lumen (lm)	1750
System wattage (W)	19,4
Watt source (W)	18
Color temperature (K)	3000
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Unified Glare Rating (U.G.R. <)	16

Physical specifications

Optic device	Mirror-metallized thermoplastic material

Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Dimmable	Dimmable on the mains
Voltage (V)	220/240
Frequency (Hz)	50/60

Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Light beam	20°

Weight and dimension

Length (mm)	175
Height (mm)	232
Diameter (mm)	67
Weight (Kg)	1

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

Datasheet

Accessories

Product Code	28-9004-30
Name	Snoot

Product Code	28-4080-30
Name	Honeycomb, to be used with snoot code 28-9004-30

Product Code	28-3905-47
Name	Closing screen in clear thermoplastic

Product Code	14768
Name	Adapter for plasterboard to be used with cod.14769

Product Code	14769
Name	Ceiling Adapter