


## Perfetto Compact LKM Cut-Phase 18W 2700K CRI85 20°

Design:



IP 20



Product Code	Color
--------------	-------

751-1613CYMD-21	Mat white
-----------------	-----------

### General specifications

Product type	Track lights
Mounting type	LKM 3-phase track
Indoor/Outdoor light	Indoor
Description	Spotlight for LKM 3-phase electrified tracks with Cut-Phase power supply, specially developed for high efficiency COB LEDs. Optical devices for better visual comfort are available.
Applications	Showrooms , Shops , Retail , Museums

### Lighting specifications

**i** Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 2301lm 18W 2700K CRI85
Nominal lumens on thermal regime (lm)	2301
LOR	72.9
Delivered lumen (lm)	1750
System wattage (W)	19,4
Watt source (W)	18
Color temperature (K)	2700
CRI	CRI 85
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Unified Glare Rating (U.G.R. <)	16

### Physical specifications

Optic device	Mirror-metallized thermoplastic material
--------------	--

### Electrical specifications

Driver availability	Included
Driver mounting	Integrated
Dimmable	Dimmable on the mains
Voltage (V)	220/240
Frequency (Hz)	50/60

### Optical specifications

Light distribution	Symmetric
Emission	Direct
Orientation	It can rotate up to 355° around the vertical axis and pivot up to 90° upwards.
Light beam	20°

### Weight and dimension

Length (mm)	175
Height (mm)	232
Diameter (mm)	67
Weight (Kg)	1

Power tolerance ± 5% - Luminous flux tolerance ± 5% - Measurement uncertainty ± 10% - Ta: 25°C

## Accessories

---



Product Code 28-9004-30  
Name Snoot



Product Code 28-4080-30  
Name Honeycomb, to be used with snoot code 28-9004-30



Product Code 28-3905-47  
Name Closing screen in clear thermoplastic



Product Code 14768  
Name Adapter for plasterboard to be used with cod.14769



Product Code 14769  
Name Ceiling Adapter

---

Power tolerance  $\pm 5\%$  - Luminous flux tolerance  $\pm 5\%$  - Measurement uncertainty  $\pm 10\%$  - Ta: 25°C