

PANNELLI Round

Round 182x39mm



INFORMAZIONI PRODOTTO:

PRODUCT INFORMATIONS:

Unità: mm
Unit: mm

Codice d'acquisto: **15540-IO**

Purchase code:

P/N: **PN00966**

Grado IP:

IP grade:

IP20

Alimentazione:

Voltage supply:

220-240Vac 50-60 Hz

Potenza:

Power:

12W

Alimentatore:

Driver:

Driver SELV (incluso, interno al corpo lampada / included, inside body lamp)

Dimmerabile:

Dimmable:

No

Sorgente luminosa:

Light source:

LED SMD

CCT/ Colore:

CCT/ Colour:

4000K

Flusso:

Flux:

935lm

Fascio:

Beam:

120°

CRI:

>80

Tolleranza cromatica:

Chromatic tolerance:

3SDCM

Fattore di abbagliamento:

Glare rating:

UGR<22

Gruppo di rischio fotobiologico:

Photobiological hazard group:

Rg0

Vita utile:

Lifetime:

L70B10@45000

Fissaggio:

Fixing:

Plafone / Ceiling

Temperatura operativa:

Operating temperature:

-10°C (min) - +30°C (max)

Classe energetica:

Energetic class:

Prodotto contenente una sorgente luminosa di classe <F> (non sostituibile)

Product contained a light source of energy class <F> (not replaceable)

Norme:

Standards:

CEI EN 60598-1


(General requirements for luminaires incorporating electric light sources for operation from supply voltages up to 1000V)

CEI EN 60598-2-03

(Particular requirements - Luminaires for road and street lighting)

IEC TR 62778:2014

(Application of IEC 62471 for the assesment of blue liht hazard to light source and luminaires)



ø182



39

